## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: TRIO Leuchten GmbH

Supplier's address: Master data, Gut Nierhof 17, 59757 Arnsberg NRW, DE

## Model identifier: 956-88

## Type of light source:

Anti-glare shield:	No	Dimmable:	Yes
High luminance light source:	No		
Colour-tuneable light source:	No	Envelope:	-
Mains or non-mains:	NMLS	Connected light source (CLS):	No
(or other electric interface)	5010		
Light source cap-type	GU10		
Lighting technology used:	LED	Non-directional or directional:	DLS

Froduct parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
•.	mption in on- 100 h), rounded st integer	7	Energy efficiency class	G		
indicating if it r in a sphere (3	us flux (фuse), refers to the flux 60º), in a wide in a narrow cone	360 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 200		
On-mode p expressed in W	oower (P <sub>on</sub> ),	6,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
for CLS, expre	ndby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer dimensions without	Height	73	Spectral power	See image		
	Width	50	distribution in the	in last page		
	Depth	50	1	Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	33			
		Chromaticity coordinates (x and y)	0,506 0,415			
Parameters for directional light sources:						
Peak luminous intensity (cd)	300	Beam angle in degrees, or the range of beam angles that can be set	60			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	2	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-' : not applicable;

(b)<sub>'-'</sub> : not applicable;

