## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name or trade mark: TRIO Leuchten GmbH						
Supplier's address: Master data, Gut Nierhof 17, 59757 Arnsberg NRW, DE						
Model identifie	r: 989-400					
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		E14				
(or other electri	ic interface)					
Mains or non-mains:		MLS	Connected light source (CLS):	No		
Colour-tuneable	e light source:	No	Envelope:	-		
High luminance	light source:	No				
Anti-glare shield:		No	Dimmable:	No		
		Product parar	neters			
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		4	Energy efficiency class	E		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode power (P <sub>on</sub> ), expressed in W		4,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	-		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	78	Spectral power	See image		
dimensions	Width	45	distribution in the	in last page		
without	Depth	45		Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	40			
		Chromaticity	0,460			
		coordinates (x and y)	0,420			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	12	Survival factor	0,90			
the lumen maintenance factor	0,93					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9			

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

