Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name or trade mark: TRIO Leuchten GmbH						
Supplier's address: Master data, Gut Nierhof 17, 59757 Arnsberg NRW, DE						
Model identifie	r: 904-479					
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		E27				
(or other electri	ic interface)					
Mains or non-mains:		MLS	Connected light source (CLS):	Non		
Colour-tuneable light source:		Non	Envelope:	-		
High luminance light source:		Non				
Anti-glare shield:		Non	Dimmable:	No		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		4	Energy efficiency class	F		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		360 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode power (P _{on}), expressed in W		4,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	140	Spectral power	See image		
dimensions without	Width	95	distribution in the	in last page		
	Depth	95		 		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	Oui	If yes, equivalent power (W)	33		
		Chromaticity	0,460		
		coordinates (x and y)	0,420		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	8	Survival factor	0,90		
the lumen maintenance factor	0,93				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9		

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

