Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: TRIO Leuchten GmbH

Supplier's address: Master data, Gut Nierhof 17, 59757 Arnsberg NRW, DE

Model identifier: 989-60

Type of light source:

| Lighting technology used: | LED | Non-directional or directional: | NDLS | | | |
|-------------------------------|-----|---------------------------------|------|--|--|--|
| Light source cap-type | E14 | | | | | |
| (or other electric interface) | | | | | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | Non | | | |
| Colour-tuneable light source: | Non | Envelope: | - | | | |
| High luminance light source: | Non | | | | | |
| Anti-glare shield: | Non | Dimmable: | No | | | |
| Product parameters | | | | | | |

| | | | lieters | | | |
|--|-----------------------------------|-------------------------|---|--------------|--|--|
| Parameter | | Value | Parameter | Value | | |
| General product parameters: | | | | | | |
| Energy consum mode (kWh/100 up to the neares | 00 h), rounded | 5 | Energy efficiency class | F | | |
| Useful luminou indicating if it re in a sphere (36 cone (120 ^o) or in (90 ^o) | efers to the flux 50°), in a wide | 470 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 | | |
| On-mode p expressed in W | ower (P _{on}), | 4,9 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | | |
| Networked stand for CLS, expres rounded to the s | sed in W and | - | Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set | 80 | | |
| Outer | Height | 100 | Spectral power | See image | | |
| dimensions | Width | 37 | distribution in the | in last page | | |
| without | Depth | 37 | 1 | Dage 1 / 2 | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | | | | |
|--|------|---|----------------|--|--|--|
| Claim of equivalent power ^(a) | Oui | If yes, equivalent power (W) | 40 | | | |
| | | Chromaticity coordinates (x and y) | 0,440 0,403 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 5 | Survival factor | 0,90 | | | |
| the lumen maintenance factor | 0,96 | | | | | |
| Parameters for LED and OLED mains light sources: | | | | | | |
| displacement factor (cos φ1) | 0,90 | Colour consistency in McAdam ellipses | 6 | | | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | lf yes then replacement claim (W) | - | | | |
| Flicker metric (Pst LM) | 1,0 | Stroboscopic effect metric (SVM) | 0,9 | | | |

(a)'-' : not applicable;

(b)'_-' : not applicable;

