## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources							
Supplier's name or trade mark: REALITY Leuchten GmbH							
Supplier's address: Master data, Gut Nierhof 17, 59757 Arnsberg, DE							
Model identifier: R988-880							
Type of light so	urce:						
Lighting technology used:		LED	Non-directional or directional:	NDLS			
Light source cap-type		E27					
(or other electri	ic interface)						
Mains or non-mains:		MLS	Connected light source (CLS):	Non			
Colour-tuneable light source:		Non	Envelope:	-			
High luminance light source:		Non					
Anti-glare shield:		Non	Dimmable:	Yes			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		7	Energy efficiency class	E			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700			
On-mode power (P <sub>on</sub> ), expressed in W		6,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80			
Outer	Height	140	Spectral power	See image			
dimensions without	Width	64	distribution in the	in last page			
without	Depth	64					

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>		Oui	If yes, equivalent power (W)	60			
			Chromaticity	0,460			
			coordinates (x and y)	0,411			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		2	Survival factor	0,90			
the lumen maintenance factor		0,90					
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)		0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)		1,0	Stroboscopic effect metric (SVM)	0,9			

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

