## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources  |                   |                         | io 13 With regula to energ   | 8, 14208 018 |
|--|-------------------|-------------------------|--|--------------|
| Supplier's name  | e or trade mark:  | TRIO Leuchten Gmb       | Н  |              |
| Supplier's addr  | ess: Master data, | , Gut Nierhof 17, 59    | 757 Arnsberg NRW, DE   |              |
| Model identifie  | er: 904-454       |                         |  |              |
| Type of light so   | urce:             |                         |  |              |
| Lighting techno  | logy used:        | LED                     | Non-directional or directional:  | NDLS         |
| Light source cap-type (or other electric interface)  |                   | E27                     |  |              |
| Mains or non-mains:  |                   | MLS                     | Connected light source (CLS):  | No           |
| Colour-tuneable light source:  |                   | No                      | Envelope:  | -            |
| High luminance light source:   |                   | No                      |  |              |
| Anti-glare shield:   |                   | No                      | Dimmable:  | No           |
| Product parameters   |                   |                         |  |              |
| Parameter  |                   | Value                   | Parameter  | Value        |
|  |                   | General product p       | parameters:  |              |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |                   | 4                       | Energy efficiency class  | F            |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |                   | 140 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000        |
| On-mode power (P <sub>on</sub> ), expressed in W   |                   | 4,0                     | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00         |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |                   | -                       | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80           |
| Outer<br>dimensions  | Height            | 135                     | Spectral power   | See image    |
|  | Width             | 95                      | distribution in the  | in last page |
| without  | Depth             | 95                      |  | Pagina 1 /   |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)                      |      | range 250 nm to 800<br>nm, at full-load |       |  |  |  |
|---|------|---|-------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>  | Sì   | If yes, equivalent power (W)            | 15    |  |  |  |
|   |      | Chromaticity                            | 0,437 |  |  |  |
|   |      | coordinates (x and y)                   | 0,404 |  |  |  |
| Parameters for LED and OLED light sources:  |      |   |       |  |  |  |
| R9 colour rendering index value   | 4    | Survival factor                         | 0,90  |  |  |  |
| the lumen maintenance factor  | 0,96 |   |       |  |  |  |
| Parameters for LED and OLED mains light sources:  |      |   |       |  |  |  |
| displacement factor (cos φ1)  | 0,00 | Colour consistency in McAdam ellipses   | 6     |  |  |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replacement claim (W)       | -     |  |  |  |
| Flicker metric (Pst LM)   | 1,0  | Stroboscopic effect metric (SVM)        | 0,9   |  |  |  |

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

