Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

	TRIO Leuchten Gmb	757 Arnsberg NRW, DE	
rce:		<u> </u>	
ogy used:			
	LED	Non-directional or directional:	NDLS
type interface)	E14		
ains:	MLS	Connected light source (CLS):	No
light source:	No	Envelope:	-
ight source:	No		
	No	Dimmable:	No
	<u>_</u>	meters	
	Value	Parameter	Value
0 h), rounded	2	Energy efficiency class	E
fers to the flux 0º), in a wide a narrow cone	250 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
ower (P _{on}),	2,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
sed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Height	98	Spectral power	See image
Width	37	distribution in the	in last page
	light source: ight	light source: No ight source: No Product para Value General product para Value On h), rounded to integer so flux (физе), fers to the flux on a narrow cone On h), in a wide a narrow cone On h), rounded to integer so flux (puse), fers to the flux on a narrow cone On h), rounded to integer so flux (puse), fers to the flux on a para for a second in the second of th	MLS Connected light source (CLS): light source: No Envelope: ight source: No Dimmable: Product parameters Value Parameter Parameter General product parameters: ption in on- 100 h), rounded t integer s flux (фuse), fers to the flux (O²), in a wide a narrow cone Sphere (360°) Dimmable: Product parameters Energy efficiency class Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set Diver (Pon), 2,0 Standby power (Psb), expressed in W and rounded to the second decimal Standby power (Pnet) and rounded to the nearest integer, or the range of CRIvalues that can be set Height 98 Spectral power distribution in the

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	Sì	If yes, equivalent power (W)	25		
		Chromaticity	0,460		
		coordinates (x and y)	0,420		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	16	Survival factor	0,90		
the lumen maintenance factor	0,93				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	:	If yes then replacement claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9		

(a)'-': not applicable;

(b)_{'-'} : not applicable;

