Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources		2,11011 (20) 2013, 2	ors with regard to energ	6) idaeiii. 6 o i i 6.11	
Supplier's name	or trade mark:	TRIO Leuchten Gmb	Н		
Supplier's addre	ess: Master data,	Gut Nierhof 17, 59	757 Arnsberg NRW, DE		
Model identifier	r: 985-6810				
Type of light sou	ırce:				
Lighting technology used:		LED	Non-directional or directional:	NDLS	
Light source cap-type (or other electric interface)		E27			
Mains or non-mains:		MLS	Connected light source (CLS):	Nee	
Colour-tuneable light source:		Nee	Envelope:	-	
High luminance light source:		Nee			
Anti-glare shield:		Nee	Dimmable:	No	
Product parameters					
Parameter		Value	Parameter	Value	
		General product p	parameters:		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		8	Energy efficiency class	F	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700	
On-mode power (P _{on}), expressed in W		8,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer	Height	170	Spectral power	See image	
dimensions	Width	125	distribution in the	in last page	
without	Depth	125		Pagina 1 /	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Ja	If yes, equivalent power (W)	60			
		Chromaticity	0,460			
		coordinates (x and y)	0,420			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	8	Survival factor	0,90			
the lumen maintenance factor	0,93					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9			

(a)'-': not applicable;

(b)_{'-'} : not applicable;

