Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources					
Supplier's name	e or trade mark:	TRIO Leuchten Gmb	Н		
Supplier's address: Master data, Gut Nierhof 17, 59757 Arnsberg NRW, DE					
Model identifie	er: 989-279				
Type of light so	urce:				
Lighting technology used:		LED	Non-directional or directional:	NDLS	
Light source cap-type		E14			
(or other electri	ic interface)				
Mains or non-mains:		MLS	Connected light source (CLS):	Nee	
Colour-tuneable	e light source:	Nee	Envelope:	-	
High luminance	light source:	Nee			
Anti-glare shield:		Nee	Dimmable:	No	
Product parameters					
Parameter		Value	Parameter	Value	
		General product p	arameters:		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		2	Energy efficiency class	E	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		250 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700	
On-mode prespressed in W	oower (P _{on}),	2,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer	Height	98	Spectral power	See image	
dimensions	Width	37	distribution in the	in last page	
without	Depth	37		 	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	Ja	If yes, equivalent power (W)	25		
		Chromaticity	0,460		
		coordinates (x and y)	0,420		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	16	Survival factor	0,90		
the lumen maintenance factor	0,93				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replacement claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9		

(a)'_-' : not applicable;

(b)_{'-'} : not applicable;

