## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: TRIO Leuchten GmbH

Supplier's address: Master data, Gut Nierhof 17, 59757 Arnsberg NRW, DE

## Model identifier: 989-479

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	E14				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	Nee		
Colour-tuneable light source:	Nee	Envelope:	-		
High luminance light source:	Nee				
Anti-glare shield:	Nee	Dimmable:	No		
Product parameters					

Parameter	Value	Darameter	Value		
rarameter		Parameter	value		
General product parameters:					
Energy consumption in mode (kWh/1000 h), rour up to the nearest integer		Energy efficiency class	F		
Useful luminous flux ( indicating if it refers to the in a sphere (360°), in a cone (120°) or in a narrow (90°)	flux Sphere (360°) vide	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode power ( expressed in W	P <sub>on</sub> ), 4,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked standby power for CLS, expressed in W rounded to the second dec	and	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer Height	98	Spectral power	See image		
dimensions Width	35	distribution in the	in last page		
without Depth	35		Pagina 1/3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power <sup>(a)</sup>	Ja	If yes, equivalent power (W)	40		
		Chromaticity coordinates (x and y)	0,460 0,420		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	12	Survival factor	0,90		
the lumen maintenance factor	0,93				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9		

(a)'-' : not applicable;

(b)'\_-' : not applicable;

