## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources  |                   |                         |  |              |
|--|-------------------|-------------------------|--|--------------|
| Supplier's name  | e or trade mark:  | TRIO Leuchten Gmb       | Н  |              |
| Supplier's addr  | ess: Master data, | Gut Nierhof 17, 59      | 757 Arnsberg NRW, DE   |              |
| Model identifie  | er: 906-879       |                         |  |              |
| Type of light so   | urce:             |                         |  |              |
| Lighting technology used:  |                   | LED                     | Non-directional or directional:  | NDLS         |
| Light source cap   | o-type            | E27                     |  |              |
| (or other electr   | ic interface)     |                         |  |              |
| Mains or non-mains:  |                   | MLS                     | Connected light source (CLS):  | Não          |
| Colour-tuneable  | e light source:   | Não                     | Envelope:  | -            |
| High luminance   | light source:     | Não                     |  |              |
| Anti-glare shield  | d:                | Não                     | Dimmable:  | Yes          |
|  |                   | Product parar           | meters   |              |
| Parameter  |                   | Value                   | Parameter  | Value        |
|  |                   | General product p       | arameters:   |              |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |                   | 8                       | Energy efficiency class  | G            |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |                   | 560 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700        |
| On-mode power (P <sub>on</sub> ), expressed in W   |                   | 8,0                     | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00         |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |                   | <del>-</del>            | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80           |
| Outer  | Height            | 320                     | Spectral power   | See image    |
| dimensions   | Width             | 180                     | distribution in the  | in last page |
| without  | Depth             | 180                     |  | Página 1 / 3 |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)                      |      | range 250 nm to 800<br>nm, at full-load |       |  |  |  |
|---|------|---|-------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>  | Sim  | If yes, equivalent power (W)            | 45    |  |  |  |
|   |      | Chromaticity                            | 0,460 |  |  |  |
|   |      | coordinates (x and y)                   | 0,411 |  |  |  |
| Parameters for LED and OLED light sources:  |      |   |       |  |  |  |
| R9 colour rendering index value   | 51   | Survival factor                         | 0,90  |  |  |  |
| the lumen maintenance factor  | 0,96 |   |       |  |  |  |
| Parameters for LED and OLED mains light sources:  |      |   |       |  |  |  |
| displacement factor (cos φ1)  | 0,50 | Colour consistency in McAdam ellipses   | 6     |  |  |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replacement claim (W)       | -     |  |  |  |
| Flicker metric (Pst LM)   | 1,0  | Stroboscopic effect metric (SVM)        | 0,9   |  |  |  |

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

