## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources			o 13 With regula to energ	B) 144 C 116 C 116 C 1
Supplier's name	e or trade mark:	TRIO Leuchten Gmb	Н	
Supplier's addr	ess: Master data,	Gut Nierhof 17, 59	757 Arnsberg NRW, DE	
Model identifie	er: 983-3279			
Type of light so	urce:			
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)		E14		
Mains or non-mains:		MLS	Connected light source (CLS):	Não
Colour-tuneable	e light source:	Não	Envelope:	-
High luminance	light source:	Não		
Anti-glare shield	d:	Não	Dimmable:	No
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		2	Energy efficiency class	E
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		225 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P <sub>on</sub> ), expressed in W		2,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		<del>-</del>	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without	Height	78	Spectral power	See image
	Width	45	distribution in the	in last page
	Depth	45		Página 1 /

separate control gear, lighting control parts		range 250 nm to 800 nm, at full-load					
and non-							
lighting							
control parts,							
if any (millimetre)							
Claim of equivalent power <sup>(a)</sup>	Sim	If yes, equivalent power (W)	25				
		Chromaticity	0,460				
		coordinates (x and y)	0,420				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	16	Survival factor	0,90				
the lumen maintenance factor	0,93						
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6				
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-				
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9				

(a)'-': not applicable;

(b)<sub>'-'</sub> : not applicable;

