## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: TRIO Leuchten GmbH

Supplier's address: Master data, Gut Nierhof 17, 59757 Arnsberg NRW, DE

## Model identifier: 987-2400

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	E27					
(or other electric interface)						
Mains or non-mains:	MLS	Connected light source (CLS):	Não			
Colour-tuneable light source:	Não	Envelope:	-			
High luminance light source:	Não					
Anti-glare shield:	Não	Dimmable:	No			
Product parameters						

		•	L	1		
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumpti mode (kWh/1000 up to the nearest in	h), rounded	4	Energy efficiency class	E		
Useful luminous f indicating if it refer in a sphere (360°) cone (120°) or in a (90°)	s to the flux , in a wide	470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode powe expressed in W	er (P <sub>on</sub> ),	4,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked standby for CLS, expressed rounded to the seco	I in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer He	eight	105	Spectral power	See image		
	idth	60	distribution in the	in last page		
without De	epth	60	1			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	Sim	If yes, equivalent power (W)	40			
		Chromaticity coordinates (x and y)	0,460 0,420			
Parameters for LED and OLED lig	ht sources:					
R9 colour rendering index value	6	Survival factor	0,90			
the lumen maintenance factor	0,93					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	-	Stroboscopic effect metric (SVM)	-			

(a)'-' : not applicable;

(b)'\_-' : not applicable;

