Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources							
Supplier's name or trade mark: REALITY Leuchten GmbH							
Supplier's address: Master data, Gut Nierhof 17, 59757 Arnsberg, DE							
Model identifier: R983-88							
Type of light source:							
Lighting technology used:		LED	Non-directional or directional:	NDLS			
Light source cap-type		E14					
(or other electri	ic interface)						
Mains or non-mains:		MLS	Connected light source (CLS):	Não			
Colour-tuneable light source:		Não	Envelope:	<u>-</u>			
High luminance light source:		Não					
Anti-glare shield:		Não	Dimmable:	Yes			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		6	Energy efficiency class	F			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode power (P _{on}), expressed in W		5,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80			
Outer	Height	108	Spectral power	See image			
dimensions without	Width	37	distribution in the	in last page			
	Depth	37		 Página 1 / 3			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)		Sim	If yes, equivalent power (W)	40			
			Chromaticity	0,437			
			coordinates (x and y)	0,404			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		2	Survival factor	0,90			
the lumen maintenance factor		0,93					
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)		0,00	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)		1,0	Stroboscopic effect metric (SVM)	0,9			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

