Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: REALITY Leuchten GmbH

Supplier's address: Master data, Gut Nierhof 17, 59757 Arnsberg, DE

Model identifier: R983-88

Type of light source:

(or other electric interface) Mains or non-mains:	MLS	Connected light source (CLS):	Nu
Colour-tuneable light source:	Nu	Envelope:	-
High luminance light source:	Nu		
Anti-glare shield:	Nu	Dimmable:	Yes

		i loudet para					
Parameter		Value	Parameter	Value			
General product parameters:							
•.	mption in on- 000 h), rounded est integer	6	Energy efficiency class	F			
indicating if it in a sphere (3	pus flux (φuse), refers to the flux 860º), in a wide in a narrow cone	470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode expressed in W	power (P _{on}), /	5,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
for CLS, expre	ndby power (P _{net}) essed in W and e second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			
Outer	Height	108	Spectral power	See image			
dimensions	Width	37	distribution in the	in last page			
without	Depth	37					
			•	Dagina 1 / 3			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Da	If yes, equivalent power (W)	40			
		Chromaticity coordinates (x and y)	0,437 0,404			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	2	Survival factor	0,90			
the lumen maintenance factor	0,93					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,00	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9			

(a)'-' : not applicable;

(b)'_-' : not applicable;

